

# AP-LD9687154800

## Industrial Monitor, 15" 1600 nits, TFT, AC Adapter, VGA, AV, Housing



### Specifications

System	
Form Factor	Industrial Monitor
OS Support	MS DOS, Windows® 2000, Windows® XP
Display	
Size	15"
Resolution	1024 x 768
Type	TFT
Max. Colors	262K
Dot Size	0.297 x 0.297
Luminance	1600 nits
Contrast Ratio	400:1
Viewing Angle (Typical)	140° /120°
Back Light MTBF	50,000 hrs
Brightness Control	Yes
Source	VGA

### Features

- Wide Viewing Angle
- Fast Response Time
- High Contrast Ratio
- Very High Brightness
- Sun-light Readable

Mechanical and Environmental	
Power Requirement	115/230 V AC
Operating Temperature	32°F ~ 122°F (0°C ~ 50°C)
Operating Humidity	90%
Storage Humidity	95%
Vibration	1.5G, 10Hz ~ 200Hz ~ 10 Hz 30 mins for each Axis (X, Y, Z)
Shock	50G/20ms, ±X, ±Y, ±Z Half-sin, one time
EMC	150pF, 150Ω, 10kV, 1 second, 9 position on the panel, 10 times each place
Dimension	15.3"(W) x 12.8"(H) x 2.4"(D) (389mm x 325mm x 60.5mm)
Construction	Heavy-duty steel chassis
Mounting	VESA 75
Front Panel Color	Black
Net Weight	8.62 lb (3.92 kg)

### Ordering Information

- AP-LD9687154800**  
Industrial Monitor, 15" 1600 nits, TFT, AC Adapter, VGA, AV, Housing
- AP-LD9687154802**  
Industrial Monitor, 15" 1600 nits, TFT, AC Adapter, VGA, AV, R-TS, Housing

# AP-LD9687174501

## Industrial Monitor, 17" 1000 nits, TFT, AC Adapter, VGA, AV, Housing



### Specifications

System	
Form Factor	Industrial Monitor
OS Support	MS DOS, Windows® 2000, Windows® XP
Display	
Size	17"
Resolution	1280 x 1024
Type	TFT
Max. Colors	262K
Dot Size	0.264 x 0.264
Luminance	1000 nits
Contrast Ratio	500:1
Viewing Angle (Typical)	160° /150°
Back Light MTBF	40,000 hrs
Brightness Control	Yes
Source	VGA

### Features

- Wide Viewing Angle
- Fast Response Time
- High Contrast Ratio
- Very High Brightness
- Sun-light Readable

Mechanical and Environmental	
Power Requirement	115/230 V AC
Operating Temperature	32°F ~ 122°F (0°C ~ 50°C)
Operating Humidity	90%
Storage Humidity	95%
Dimension	17.2"(W) x 14.7"(H) x 2.4"(D) (436mm x 373mm x 61.5mm)
Vibration	1.5G, 10Hz ~ 200Hz ~ 10 Hz 30mins for each Axis (X, Y, Z)
Shock	50G/20ms, ±X, ±Y, ±Z Half-sin, one time
EMC	150pF, 150Ω, 10kV, 1 second, 9 position on the panel, 10 times each place
Construction	Heavy-duty steel chassis
Mounting	VESA 75
Front Panel Color	Black
Net Weight	10.7 lb (4.86 kg)

### Ordering Information

- AP-LD9687174501**  
Industrial Monitor, 17" 1000 nits, TFT, AC Adapter, VGA, AV, Housing
- AP-LD9687174502**  
Industrial Monitor, 17" 1000 nits, TFT, AC Adapter, VGA, AV, R-TS, Housing