


42" CCFL Specifications



Key Features

- Sunlight Readable
- 16:9 Wide
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- 20 CCFL



ALF/ALH/SLO/SLD4212/15

Model No.	ALF4212/15	ALH4212/15	SLO4212/15	SLD4212/15
LCD Display	42" WXGATFT LCD Module			
Display Area	930.25 x 530.01mm			
Brightness	500 cd/m ² / 1000 cd/m ²			
Resolution	1366x768 (WXGA)			
Contrast Ratio	1500 : 1/1700:1			
Pixel Pitch (mm)	0.681(H) x 0.681(V)			
Viewing Angle	+89 ~-89 (H), +89 ~-89 (V)			
Display Colors	16.7M colors			
Response Time	8ms (Typical)			
Sync	LVDS			
Power Consumption	193W/ 240W	198W/ 245W	198W/ 245W	198W/ 245W
Inverter	DPS-290BP			
Control Board (Optional)		AD5621GA AD5621GD AD5766GDVA	AD5621GA AD5621GD AD5766GDVA	AD5621GA AD5621GD AD5766GDVA
F / R Control Button		5 Key	4 Key	
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock...		
Dimensions (WxHxD)mm	967x558.6x64.9	967x558.6x64.9	1007x558.6x86.6	967x558.6x86.6
Weight	7.9kg	8.5kg	TBA	TBA
Optional	AOT	Touch	Waterproof	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA
AD5621GA	VGA+Audio
AD5621GD	VGA+DVI
AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
F / R Control Button	5 Key / 4 Key (Optional)
5 Key	Power Switch, Menu, Select (+,-), Auto
4 Key	Power Switch, Menu, Select (+,-)



Your Industrial Solutions Partner!